



altro

Designed for possibilities.
Made for people.

Altro Serenade™

Smooth flooring with enhanced sound reduction and high underfoot comfort



discover [altro.com](https://www.altro.com)

LITERATURE>DATASHEET

3.9mm
thick

6'7"
width

66'
length


sheet
format



Rhythm SE3907
WR428 / AM200 LRV 50




Cymbal SE3910
WR431 / AM200 LRV 53



Mezzo SE3913
WR434 / AM200 LRV 49




Metronome SE3914
WR435 / AM200 LRV 26



Cadence SE3908
WR429 / AM200 LRV 26




Maestro SE3903
WR424 / AM200 LRV 32




Tambourine SE3911
WR432 / AM200 LRV 26



Finale SE3902
WR423 / AM200 LRV 20



Bridge SE3912
WR433 / AM200 LRV 15



Octave SE3915
WR436 / AM200 LRV 17




Prelude SE3923
WR444 / AM200 LRV 24




Saxophone SE3920
WR441 / AM200 LRV 30



March SE3925
WR446 / AM200 LRV 37



Encore SE3929
WR450 / AM200 LRV 24



Bar SE3931
WR452 / AM200 LRV 17



Altro Serenade

Commercial-grade, smooth, sheet vinyl with acoustic backing

Slip resistance

Static coefficient of friction		ASTM D2047	.7 dry, .8 wet
Ramp test		DIN 51130	R10

Specifications

Thickness	3.9mm		
Roll dimensions	6'7" x 66' 2.0m x 20m		
Weight	5.34 lbs/yd ² 2.9 kg/m ²		
Wear layer	.7mm		
Cleaning technology		Altro Easyclean	
Warranty		10 years	
Static load limit		ASTM F970	500 psi
Sound insulation		ISO 10140	19dB
		IIC rating	54
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with 24% rapidly renewable bio-based content.	
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing. Altro Easyclean incorporated into top layer for exceptional cleanability.		
Backing	Blown PVC backing.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altrofloors.com/downloads , training clinic information at altrofloors.com/training . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altrofloors.com/downloads . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, Altro Serenade and Altro Easyclean are all trademarks of Altro Limited. Folder content was correct at time of print. Altro reserves the right to change any detail. Please consult your sales representative for the latest product information.
© Copyright Altro USA 2017

LEED facts



LEED v4

This product may help contribute to the following credits

Altro Serenade 7

	Materials and resources Renewable bio-based content	1
	Materials and resources Environmental product declaration	1
	Materials and resources Health product declaration	1
	Environmental quality Low emitting materials, flooring	3
	Environmental quality Low emitting materials, adhesives	1

Discover more of our sustainability story and credentials at altro.com/sustainability

Follow us



USA 800 377 5597

CANADA 800 565 4658

support@altrofloors.com

www.altro.com