



Ondervloer
Unterlagsboden
Underlay



THE BEST UNDERLAY IN COMBINATION WITH LVT DESIGNFLOOR CLICK

☆☆ = goed / gut / good
☆☆☆☆ = beste / best

Materiaal / Material	HD Rubber 1600			
m ² per rol / pro Rolle / per roll	10 m²			
Dikte / Stärke / Thickness	1,2 mm	EN 823	Tolerantie / Toleranz / Tolerance	+/- 15%
Lengte / Länge / Length	10,0 mtr	EN 822	Tolerantie / Toleranz / Tolerance	-0 / +0,5m
Breedte / Breite / Width	1,0 mtr	EN 822	Tolerantie / Toleranz / Tolerance	-10 / +10mm
Densiteit / Densität / Density	+/- 1600 Kg/m ³		Tolerantie / Toleranz / Tolerance	+/- 80 Kg/m ³
Gewicht / Weight per rol/rolle/roll	+/- 19,2 Kg		Tolerantie / Toleranz / Tolerance	+/- 5%

	Requirements	Norm	Result	
Contactgeluidsreductie (IS) Trittschallreduzierung Impact Sound reduction	ΔLw > 18 dB	EN 140-8 / 717-2 icw LVT designfloor click	☆☆☆☆	
Loopgeluidreductie (RWS) Gehrschallreduzierung Reflected Walking Sound reduction	class RWS 3 < 20 sone	CEN/TS 16354	☆☆☆☆	
Warmteweerstand (R) Wärmedurchlasswiderstand Thermal insulation	0,01 m ² K/W	EN 12667	☆☆☆☆	
Dampdichtheid (Sd) Wasserdampfdurchlässigkeit Water vapour diffusion resistance	> 75m	EN 12086/12572	☆☆☆☆	
Drukweerstand (CS) Druckfestigkeit Compressive Strength	class CS 3 ≥ 400 kPa	EN 826 / TS 16354	☆☆☆☆	
Kruipweerstand (CC) Kriechverhalten Compressive Creep	class CC 3 > 50 kPa	EN 1606 / TS 16354	☆☆☆☆	
Dynamische belasting (DL) Dynamische Druckfestigkeit Dynamic Load	class DL 2 ≥ 100.000 cycli	EN 13793 / TS 16354	☆☆☆☆	
Bescherming tegen oneffenheden (PC) Formaanpassingsfähigkeit Punctual Conformity	≥ 0,5 mm	EN 868 / TS 16354	☆☆	
Kogelimpact (RLB) Stossbeanspruchung Protection against falling objects	Niet vastgesteld Nicht festgestellt Not detected	EN 13329	☆☆☆☆	
DIBT Bauaufsichtliche Zulassung	beantragt / applied			
Emissiewaarde VOS Emissionsverhalten VOC Emission of VOC's	A+	EN 16000-9		
Brandklasse / Fire class	beantragt / applied	EN 13501		
Recyclebaar / Recyclebar / Recyclable	ja / yes			
Afvoer / Entsorgung / waste	huisvuil / Hausmüll / house waste			

Toepassing / Anwendung / Usage

Losliggend onder LVT design clickvloeren.
Schwimmend unter LVT Designbelagsboden click.
Loose under LVT designfloors click.

